
Socket Head Cap Screw - Page 1 of 2





Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.170 inches and 0.250 inches	
Fastener Length:	
Between 0.220 inches and 0.250 inches	
Head Style:	
Flat chamfer	
Head Diameter:	
Between 0.176 inches and 0.183 inches	
Head Height:	
Between 0.108 inches and 0.112 inches	
Locking Feature:	
Strip threads	
Internal Drive Style:	
Hexagon	
Thread Diameter:	
0.112 inches	
Width Across Flats:	
Between 0.094 inches and 0.095 inches	
Thready Qty Per Inch (tpi):	
40	
Min. Tensile Strength (psi):	
80000 pounds per square inch	
Hardness Rating:	
80.0 rockwell b fastener	
Minimum Yield Strength:	
30000 pounds per square inch	
Material:	
Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel of	comp 384 fastener or
steel comp xm-7 fastener	
Surface Treatment:	
Passivate fastener	
Surface Treatment Specification:	
Astm a380 assn standard single treatment response fastener	
Thread Series Designator:	
Unrc	
Specification Data:	
80205-nas1352 professional/industrial association standard	

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-294-8591

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

