NSN 5305-01-294-9393

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-294-9393 **Thread Class:** 2a **Thread Direction:** Right-hand **Thread Length:** Between 0.438 inches and 0.520 inches **Fastener Length:** Between 0.480 inches and 0.520 inches **Head Style:** Pan **Head Diameter:** Between 0.407 inches and 0.425 inches **Head Height:** Between 0.139 inches and 0.151 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.216 inches Thready Qty Per Inch (tpi): 24 **Screw Material:** Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1025 or steel comp 1030 or steel comp 1035 or steel comp 1040 or steel comp 1045 or steel comp 1050 or steel comp 1095 or steel comp 1213 or steel comp 1115 or steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 1141 or steel comp 1144 or steel comp 1151 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp 1330 or steel comp 1548 **Screw Material Specification:**

Astm a108 assn standard all material responses

Screw Surface Treatment:

Zinc and chromate

Screw Surface Treatment Specification:

Astm b633 type 2 cl fe/zn 13 assn standard single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

3 type or 9c style

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0