## NSN 5305-01-294-9399

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-294-9399

view Offilite at https://aerobasegroup.com/histi/05005-01-254-5555
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.532 inches and 0.625 inches
Fastener Length:
Between 0.594 inches and 0.625 inches
Head Style:
Fillister
Head Diameter:
Between 0.306 inches and 0.313 inches
Head Height:
Between 0.103 inches and 0.118 inches
Locking Feature:
Patch threads
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Steel comp 4140 fastener or steel comp 8740 fastener or steel comp e4340 fastener
Material Specification:
Mil-s-5626 military specification 1st material response fastener or mil-s-6049 military specification 2nd material response fastener or
mil-s-5000 military specification 3rd material response fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unjf
Specification Data:
80205-nas1191 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-294-9399

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.