NSN 5305-01-294-9400

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-294-9400

View Online at https://aerobasegroup.com/nsn/5305-01-294-9400
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.545 inches and 0.625 inches
Fastener Length:
Between 0.595 inches and 0.625 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.176 inches and 0.183 inches
Head Height:
Between 0.108 inches and 0.112 inches
Locking Feature:
Strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.112 inches
Width Across Flats:
Between 0.094 inches and 0.095 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b fastener
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or
steel comp xm-7 fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Astm a380 assn standard single treatment response fastener
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-294-9400

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0