NSN 5305-01-295-1059



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-295-1059 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.296 inches and 0.374 inches **Fastener Length:** Between 0.515 inches and 0.562 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.686 inches and 0.762 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 8740 or steel comp 8630 **Screw Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:
Unf

Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

NSN 5305-01-295-1059

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.