## NSN 5305-01-295-3024

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-295-3024

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 1.250 inches   |
| Fastener Length:   |
| Between 1.460 inches and 1.500 inches  |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| Between 0.550 inches and 0.562 inches  |
| Head Height:   |
| Between 0.368 inches and 0.375 inches  |
| Locking Feature:   |
| Strip threads  |
| Internal Drive Style:  |
| Hexagon  |
| Thread Diameter:   |
| 0.375 inches   |
| Width Across Flats:  |
| Between 0.313 inches and 0.316 inches  |
| Thready Qty Per Inch (tpi):  |
| 16   |
| Min. Tensile Strength (psi):   |
| 80000 pounds per square inch   |
| Hardness Rating:   |
| 80.0 rockwell b fastener   |
| Minimum Yield Strength:  |
| 30000 pounds per square inch   |
| Material:  |
| Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or |
| steel comp xm-7 fastener   |
| Surface Treatment:   |
| Passivate fastener   |
| Surface Treatment Specification:   |
| Astm a380 assn standard single treatment response fastener   |
| Thread Series Designator:  |
| Unrc   |
| Specification Data:  |
| 80205-nas1352 professional/industrial association standard   |
| Shelf Life:  |

N/a

## NSN 5305-01-295-3024

Socket Head Cap Screw - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

A003b0