## NSN 5305-01-295-5108

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-295-5108

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.875 inches
Fastener Length:
Between 1.210 inches and 1.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.262 inches and 0.270 inches
Head Height:
Between 0.159 inches and 0.164 inches
Locking Feature:
Strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.164 inches
Width Across Flats:
Between 0.141 inches and 0.143 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b fastener
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or
steel comp xm-7 fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Astm a380 assn standard single treatment response fastener
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard

N/a

Shelf Life:

## NSN 5305-01-295-5108

Socket Head Cap Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0