NSN 5305-01-295-5717

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-295-5717 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.176 inches and 0.196 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.078 inches and 0.088 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.648 inches and 0.699 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Color: Black Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl 4 military specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 9c style

Shelf Life:

N/a

NSN 5305-01-295-5717

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:	
Nο	

Unit Of Measure:

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.