Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-296-0364

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.313 inches |
| Fastener Length: |
| 0.750 inches |
| Head Style: |
| Knurled no. 4 |
| Head Diameter: |
| 0.500 inches |
| Head Height: |
| 0.563 inches |
| First Diameter From Head: |
| |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.249 inches |
| Point Style: |
| Cone |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| |
| Thready Qty Per Inch (tpi): |
| |
| Externally Relieved Body Diameter Quantity: |
| |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Astm a582 assn standard single material response Surface Treatment: |
| |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unc Sholf Life: |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |

AeroBase Group

Demilitarization:

No

Fiig:

A003b0