NSN 5305-01-296-0368

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-296-0368 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.508 inches and 1.750 inches **Fastener Length:** Between 1.690 inches and 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.921 inches and 0.938 inches **Head Height:** Between 0.616 inches and 0.625 inches **Locking Feature:** Self-locking **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 37.0 rockwell c and 45.0 rockwell c **Special Features:** Material: steel comp a574; locking feature: self-locking type I per mil-dtl-18240; surface finish: phosphate per tt-c-490 type i **Surface Treatment:** Phosphate **Thread Series Designator:** Unc **Specification Or Standard:** 2 type Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-296-0368

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-1222 spec.