NSN 5305-01-296-2846

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-296-2846 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.195 inches **Fastener Length:** 0.660 inches **Head Style:** Hexagon **Head Height:** Between 0.104 inches and 0.114 inches Width Between Flats: Between 0.365 inches and 0.377 inches **Locking Feature:** Patch threads or pellet threads or strip threads **First Diameter From Head:** 0.130 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.465 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4130 fastener **Material Specification:** Mil-s-6758 cond f military specification single material response fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response fastener **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-296-2846

Externally Relieved Body Screw - Page 2 of 2



_		••	• •				
n	em	ш	112	riz	2 †1	n	٠.

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.