NSN 5305-01-296-2847

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-296-2847 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.247 inches **Fastener Length:** 2.247 inches **Head Style:** Double chamfer **Head Diameter:** 0.438 inches **Head Height:** 0.378 inches **First Diameter From Head:** Between 0.074 inches and 0.082 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Grip 1.625 in. Nom Ig; 0.135 in. Min 0.145 in maximum dia; threads on shank 0.350 in. Min 0.410 in. Maximum Ig; 0.190-32unf-2a; 96 dp raised diamond knurl head Material: Steel comp 303 **Material Specification:** Aisi assn standard single material response or astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 2 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-296-2847

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0