NSN 5305-01-296-5319

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-296-5319 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.365 inches and 0.375 inches **Fastener Length:** Between 1.985 inches and 2.015 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.615 inches and 0.635 inches **Head Height:** Between 0.672 inches and 0.704 inches **First Diameter From Head:** Between 0.225 inches and 0.235 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.365 inches and 1.385 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches **Features Provided:** Dry film lubricant Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-296-5319

Externally Relieved Body Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0