NSN 5305-01-296-6388

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-296-6388 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.375 inches **Fastener Length:** Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.312 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Color: Black Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, class 1 military specification single treatment response **Thread Series Designator:** Unrc **Specification Data:**

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-296-6388

Socket Head Cap Screw - Page 2 of 2



| ι | Jnit | Of | Measure: |
|---|-------|----|-----------|
| • | ,,,,, | • | moudai c. |

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.