NSN 5305-01-296-6651

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-296-6651 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.268 inches and 0.287 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.114 inches and 0.124 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.307 inches and 0.357 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Color: Gray Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 384 or steel comp comp 385 **Surface Treatment:** Ceramic **Surface Treatment Specification:** Mil-c-81751 type 1, cl 4 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

Demilitarization:

NSN 5305-01-296-6651

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-81751 spec.