

View Online at <https://aerobasegroup.com/nsn/5305-01-296-7806>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.408 inches and 0.500 inches

Fastener Length:

Between 0.470 inches and 0.500 inches

Head Style:

Fillister extended washer

Head Diameter:

Between 0.343 inches and 0.363 inches

Head Height:

Between 0.085 inches and 0.105 inches

Extended Washer Diameter:

Between 0.413 inches and 0.443 inches

Extended Washer Thickness:

Between 0.030 inches and 0.037 inches

Washer Quantity:

1

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Primary Washer Outside Diameter:

Between 0.413 inches and 0.443 inches

Primary Washer Style:

Flat

Primary Washer Material Thickness:

Between 0.030 inches and 0.037 inches

Color:

Green threads

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas8403 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A003b0