NSN 5305-01-296-7806

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-296-7806 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.408 inches and 0.500 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Fillister extended washer **Head Diameter:** Between 0.343 inches and 0.363 inches **Head Height:** Between 0.085 inches and 0.105 inches **Extended Washer Diameter:** Between 0.413 inches and 0.443 inches **Extended Washer Thickness:** Between 0.030 inches and 0.037 inches **Washer Quantity: Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Primary Washer Outside Diameter:** Between 0.413 inches and 0.443 inches **Primary Washer Style:**

Primary Washer Material Thickness:

Between 0.030 inches and 0.037 inches

Color:

Green threads

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Cadmium and chromate

NSN 5305-01-296-7806

Assembled Washer Screw - Page 2 of 2



Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas8403 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0