

View Online at <https://aerobasegroup.com/nsn/5305-01-297-2494>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.459 inches and 0.479 inches

Fastener Length:

Between 1.266 inches and 1.296 inches

Head Style:

Oval countersunk

Head Diameter:

Between 0.390 inches and 0.395 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Grip Length:

Between 0.615 inches and 0.635 inches

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Steel comp 8740

Material Specification:

Mil-s-6049 military specification single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488 type 2 cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.