## NSN 5305-01-297-2756

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-297-2756

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.512 inches   |
| Fastener Length:   |
| Between 0.547 inches and 0.577 inches                          |
| Head Style:  |
| Knurled no. 1  |
| Head Diameter:   |
| 0.451 inches   |
| Head Height:   |
| 0.520 inches   |
| Internal Drive Style:  |
| Slot   |
| Material Accommodated Thickness:                               |
| Between 0.094 inches and 0.155 inches                          |
| Thread Diameter:   |
| 0.190 inches   |
| Thready Qty Per Inch (tpi):                                    |
| 32   |
| Product Name:  |
| Navy special project   |
| Material:  |
| Steel comp 302 spring  |
| Material Specification:  |
| Qq-w-423 federal specification single material response spring |
| Surface Treatment:   |
| Passivate spring   |
| Surface Treatment Specification:                               |
| Qq-p-35 federal specification single treatment response spring |
| Thread Series Designator:                                      |
| Unf  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |

A003b0

## NSN 5305-01-297-2756

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-s-5059 spec.