

View Online at <https://aerobasegroup.com/nsn/5305-01-297-8235>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.298 inches and 0.348 inches

**Fastener Length:**

Between 1.246 inches and 1.276 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.325 inches and 0.385 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.928 inches and 0.948 inches

**Features Provided:**

Dry film lubricant

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Aluminum and chromate

**Surface Treatment Specification:**

Mil-c-83488 type 2 cl 3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.