## NSN 5305-01-298-2441

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-298-2441 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.364 inches and 0.414 inches **Fastener Length:** Between 0.624 inches and 0.654 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.354 inches and 0.399 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Color: Green threads Material: Iron alloy 660 **Material Specification:** Ams5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

\_\_

**Unit Of Measure:** 

## NSN 5305-01-298-2441

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0