## NSN 5305-01-298-3126

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-298-3126

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 1.250 inches   |
| Fastener Length:   |
| Between 4.440 inches and 4.500 inches                                |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| Between 0.550 inches and 0.562 inches                                |
| Head Height:   |
| Between 0.368 inches and 0.375 inches                                |
| Hole Diameter:   |
| Between 0.061 inches and 0.067 inches                                |
| Internal Drive Style:  |
| Hexagon  |
| Thread Diameter:   |
| 0.375 inches   |
| Width Across Flats:  |
| Between 0.3125 inches and 0.3160 inches                              |
| Hole Quantity:   |
| 6  |
| Hole Type:   |
| Drilled  |
| Thready Qty Per Inch (tpi):  |
| 24   |
| Min. Tensile Strength (psi):   |
| 180000 pounds per square inch  |
| Hardness Rating:   |
| 39.0 rockwell c and 45.0 rockwell c                                  |
| Hole Configuration Style:  |
| Round internal hexagon   |
| Material:  |
| Steel  |
| Surface Treatment:   |
| Cadmium and chromate   |
| Surface Treatment Specification:                                     |
| Qq-p-416 type 2 cl 2 federal specification single treatment response |
| Thread Series Designator:  |
| Unrf   |

## NSN 5305-01-298-3126

Socket Head Cap Screw - Page 2 of 2



**Specification Data:** 

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A003b0