NSN 5305-01-298-3196

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-298-3196 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.125 inches **Fastener Length:** Between 1.460 inches and 1.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.312 inches **Hole Diameter:** Between 0.044 inches and 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 45.0 rockwell c **Hole Configuration Style:** Round internal hexagon Color: Black Material: Steel **Surface Treatment:** Oxide

Surface Treatment Specification:

Mil-c-13924 class 1 military specification single treatment response

NSN 5305-01-298-3196

Socket Head Cap Screw - Page 2 of 2



| Thread Series Designator: |
|--|
| Unrc |
| Specification Data: |
| 80205-nas1352 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| Mil-std (military Standard): |

Mil-c-13924 spec.