

View Online at <https://aerobasegroup.com/nsn/5305-01-298-4832>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.554 inches and 0.604 inches

**Fastener Length:**

Between 1.314 inches and 1.344 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.703 inches and 0.762 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-8844 military specification 2nd material response or ams 6414 assn standard 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium or cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 1 cl 3 federal specification single treatment response or qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1221 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.