## NSN 5305-01-298-9668



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-298-9668 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.783 inches and 0.875 inches **Fastener Length:** Between 0.845 inches and 0.875 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Locking Feature:** Strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature **Material Specification:** Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener

#### **Surface Treatment:**

Passivate fastener

## **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response fastener

## **Thread Series Designator:**

Unrf

## **Specification Data:**

80205-nas1351 professional/industrial association standard

## Shelf Life:

N/a

#### **Unit Of Measure:**

# NSN 5305-01-298-9668

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0