NSN 5305-01-299-1917

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-299-1917

view Online at https://aerobasegroup.com/nsn/3303-01-233-1317
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.289 inches and 0.375 inches
Fastener Length:
Between 0.345 inches and 0.375 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.262 inches and 0.270 inches
Head Height:
Between 0.159 inches and 0.164 inches
Locking Feature:
Pellet threads
nternal Drive Style:
Hexagon
Thread Diameter:
0.164 inches
Width Across Flats:
Between 0.141 inches and 0.143 inches
Thready Qty Per Inch (tpi):
36
Min. Tensile Strength (psi):
30000 pounds per square inch
Hardness Rating:
30.0 rockwell b fastener
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or
steel comp xm-7 fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Jnrf
Specification Data:
30205-nas1351 professional/industrial association standard

N/a

Shelf Life:

NSN 5305-01-299-1917

Socket Head Cap Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0