NSN 5305-01-299-6586

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-299-6586 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.359 inches and 0.391 inches **Fastener Length:** Between 1.234 inches and 1.266 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.433 inches and 0.443 inches **Head Height:** Between 0.234 inches and 0.266 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.843 inches and 0.907 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Copper alloy 360 **Material Specification:** Qq-b-626 comp 22 1/2 hard federal specification single material response **Surface Treatment:** Zinc **Surface Treatment Specification:** Astm b633, type 1 cl 3 assn standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-299-6586

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0