# NSN 5305-01-299-9525

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-299-9525



## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.235 inches and 0.327 inches

#### Fastener Length:

Between 0.297 inches and 0.327 inches

#### Head Style:

Pan no. 2

Head Diameter:

Between 0.360 inches and 0.374 inches

#### Head Height:

Between 0.115 inches and 0.125 inches

#### Hole Diameter:

Between 0.060 inches and 0.068 inches

#### Internal Drive Style:

High-torque

#### **Thread Diameter:**

0.190 inches

#### Hole Quantity:

1

### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Screw Material:**

Iron alloy 660

### Screw Material Specification:

Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

#### **Screw Surface Treatment:**

Passivate

#### Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### Head Hole Configuration Style:

Round

#### Bearing Surface Of Head Surface Finish:

32.0 microinches

#### Thread Surface Finish:

32.0 microinches

#### **Special Features:**

Hole type drilled

# NSN 5305-01-299-9525

Machine Screw - Page 2 of 2



**Thread Series Designator:** 

Unjf

Specification Data:

80205-nas1216 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0