

View Online at <https://aerobasegroup.com/nsn/5305-01-300-1505>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.506 inches and 0.556 inches

**Fastener Length:**

Between 1.266 inches and 1.296 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.625 inches and 0.635 inches

**Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.740 inches and 0.760 inches

**Thready Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Tapped hole in head 0.1380-32, unjc-3b threads. Distance from top of head to injection port 0.240 inch. Injection port 0.120 in. Lg, 0.060 in.

Wide

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0