## NSN 5305-01-300-6262

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-300-6262 **Thread Direction:** Right-hand Thread Length: Between 17.10 millimeters and 20.40 millimeters Fastener Length: Between 1.60 millimeters and 20.40 millimeters **Head Style:** Flat chamfer **Head Diameter:** Between 12.70 millimeters and 13.00 millimeters **Head Height:** Between 7.83 millimeters and 8.00 millimeters **Internal Drive Style:** Hexagon **Thread Diameter:** 8.0 millimeters Width Across Flats: Between 6.020 millimeters and 6.095 millimeters Min. Tensile Strength (psi): 1220 megapascals Hardness Rating: 38.0 rockwell c and 44.0 rockwell c Minimum Yield Strength: 1100 megapascals **Thread Pitch In Millimeters:** 1.25 **External Thread Tolerance Class:** 4g6g Material: Steel property class 12.9 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** М

Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

## NSN 5305-01-300-6262

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0