NSN 5305-01-300-6262

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-300-6262

Thread Direction:
Right-hand
Thread Length:
Between 17.10 millimeters and 20.40 millimeters
Fastener Length:
Between 1.60 millimeters and 20.40 millimeters
Head Style:
Flat chamfer
Head Diameter:
Between 12.70 millimeters and 13.00 millimeters
Head Height:
Between 7.83 millimeters and 8.00 millimeters
Internal Drive Style:
Hexagon
Thread Diameter:
8.0 millimeters
Width Across Flats:
Between 6.020 millimeters and 6.095 millimeters
Min. Tensile Strength (psi):
1220 megapascals
Hardness Rating:
38.0 rockwell c and 44.0 rockwell c
Minimum Yield Strength:
1100 megapascals
Thread Pitch In Millimeters:
1.25
External Thread Tolerance Class:
4g6g
Material:
Steel property class 12.9
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
M
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
Demilitarization:
No

NSN 5305-01-300-6262

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

