

View Online at <https://aerobasegroup.com/nsn/5305-01-300-7444>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.594 inches and 0.625 inches

Fastener Length:

Between 0.219 inches and 0.250 inches

Head Style:

Pan

Head Diameter:

Between 0.302 inches and 0.322 inches

Head Height:

Between 0.105 inches and 0.115 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

6000 pounds per square inch

Screw Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022

Screw Material Specification:

66 federal standard all material responses

Screw Surface Treatment:

Zinc

Screw Surface Treatment Specification:

Astm b633, type 2 cl fe/zn 13 assn standard single treatment response

Special Features:

Screw material continue all steel comp for 1023 or 1025 or 1026 or 1029 or 1030 or 1031 or 1033 or 1034 or 1037 or 1038 or 1039 or 1040

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 9c style

Departure From Cited Document:

As modified by surface treatment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0