NSN 5305-01-301-0599



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-301-0599 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.375 inches **Fastener Length:** Between 1.940 inches and 2.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.642 inches and 0.656 inches **Head Height:** Between 0.430 inches and 0.437 inches **Hole Diameter:** Between 0.061 inches and 0.067 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.438 inches Width Across Flats: Between 0.375 inches and 0.379 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch **Hole Configuration Style:** Round internal hexagon Material: Steel **Surface Treatment:** Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response

NSN 5305-01-301-0599

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0