

View Online at <https://aerobasegroup.com/nsn/5305-01-301-2308>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.148 inches and 0.250 inches

**Fastener Length:**

Between 0.219 inches and 0.250 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.357 inches and 0.375 inches

**Head Height:**

Between 0.133 inches and 0.150 inches

**Hole Diameter:**

Between 0.060 inches and 0.068 inches

**Internal Drive Style:**

Torque set

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

1

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

Between 24.0 rockwell c and 35.0 rockwell c

**Screw Material:**

Iron alloy 660

**Screw Material Specification:**

Ams 5737 assn standard single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Head Hole Configuration Style:**

Round

**Bearing Surface Of Head Surface Finish:**

32.0 microinches

**Thread Surface Finish:**

32.0 microinches

**Special Features:**

Hole type drilled

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1101 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0