NSN 5305-01-301-2308

Machine Screw - Page 1 of 2

Between 0.148 inches and 0.250 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5305-01-301-2308

Between 0.219 inches and 0.250 inches
Head Style:
Fillister
Head Diameter:
Between 0.357 inches and 0.375 inches
Head Height:
Between 0.133 inches and 0.150 inches
Hole Diameter:
Between 0.060 inches and 0.068 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.250 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 24.0 rockwell c and 35.0 rockwell c
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Head Hole Configuration Style:
Round
Bearing Surface Of Head Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches

NSN 5305-01-301-2308 Machine Screw - Page 2 of 2

A500d0



Special Features:
Hole type drilled
Thread Series Designator:
Unjf
Specification Data:
80205-nas1101 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: