NSN 5305-01-301-7838



Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-301-7838 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.125 inches **Fastener Length:** Between 0.218 inches and 0.250 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.250 inches **Secondary Washer Outside Diameter:** Between 0.253 inches and 0.263 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.031 inches **Secondary Washer Material Thickness:** Between 0.013 inches and 0.019 inches Material:

Steel comp 302 secondary washer or steel comp 304 secondary washer

Material Specification:

Qq-s-763 cond b federal specification 1st material response fastener or qq-s-763 cond a federal specification 2nd material response fastener

Surface Treatment:

Passivate secondary washer

NSN 5305-01-301-7838

Assembled Washer Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response secondary washer

Thread Series Designator:

Unc

Specification Data:

80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.