NSN 5305-01-301-7935

Machine Screw - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5305-01-301-7935

Thread Length:
Between 0.188 inches and 0.312 inches
Fastener Length:
Between 0.250 inches and 0.312 inches
Head Style:
Fillister
Head Diameter:
Between 0.221 inches and 0.226 inches
Head Height:
Between 0.074 inches and 0.086 inches
Locking Feature:
Strip
Internal Drive Style:
Torque set
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Locking Feature Material:
Plastic polyamide
Screw Material Specification:
Ams 5737 assn standard single material response
Locking Feature Material Specification:
Mil-f-18240 military specification single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
32.0 microinches
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches

NSN 5305-01-301-7935

Machine Screw - Page 2 of 2

Mil-f-18240 spec.



Inread Series Designator:
Unjc
Specification Data:
80205-nas1191 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A500d0
Mil-std (military Standard):