NSN 5305-01-302-2374

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-302-2374 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.160 inches **Fastener Length:** 0.500 inches **Head Style: Button Head Diameter:** Between 0.250 inches and 0.262 inches **Head Height:** Between 0.063 inches and 0.073 inches **First Diameter From Head:** Between 0.089 inches and 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.340 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.078 inches and 0.079 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Iron alloy 660 **Material Specification:** Ams5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life: N/a

NSN 5305-01-302-2374

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0