

View Online at <https://aerobasegroup.com/nsn/5305-01-302-2376>

Thread Direction:

Right-hand

Thread Length:

Between 31.7 millimeters and 34.3 millimeters

Fastener Length:

Between 33.7 millimeters and 34.3 millimeters

Head Style:

Fillister

Head Diameter:

Between 9.74 millimeters and 10.00 millimeters

Head Height:

Between 5.85 millimeters and 6.00 millimeters

Internal Drive Style:

Hexagon

Thread Diameter:

6.0 millimeters

Width Across Flats:

Between 5.020 millimeters and 5.084 millimeters

Min. Tensile Strength (psi):

1100 megapascals

Thread Pitch In Millimeters:

1.0

External Thread Tolerance Class:

4h6h

Surface Finish:

0.8 micrometers threads

Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Mj

Specification Data:

80205-na0069 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0