NSN 5305-01-302-2376

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-302-2376

Thread Direction:
Right-hand
Thread Length:
Between 31.7 millimeters and 34.3 millimeters
Fastener Length:
Between 33.7 millimeters and 34.3 millimeters
Head Style:
Fillister
Head Diameter:
Between 9.74 millimeters and 10.00 millimeters
Head Height:
Between 5.85 millimeters and 6.00 millimeters
Internal Drive Style:
Hexagon
Thread Diameter:
6.0 millimeters
Width Across Flats:
Between 5.020 millimeters and 5.084 millimeters
Min. Tensile Strength (psi):
1100 megapascals
Thread Pitch In Millimeters:
1.0
External Thread Tolerance Class:
4h6h
Surface Finish:
0.8 micrometers threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Mj
Specification Data:
80205-na0069 professional/industrial association standard
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5305-01-302-2376

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0