NSN 5305-01-302-2425

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-302-2425

Thread Class
Thread Class:
2a
Thread Direction:
Right-hand Thread Laureth
Thread Length:
0.445 inches
Fastener Length:
Between 0.470 inches and 0.500 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.096 inches and 0.119 inches
Locking Feature:
Pellet or strip or patch
Internal Drive Style:
Slot
Thread Diameter:
0.060 inches
Thready Qty Per Inch (tpi):
80
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Screw Material:
Steel comp 1010
Locking Feature Material:
Plastic polyamide
Screw Material Specification:
Astm a576 assn standard single material response or astm a108 assn standard single material response
Locking Feature Material Specification:
Mil-f-18240 military specification single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Specification Data:
80205-nas662 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-302-2425

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-f-18240 spec.