

View Online at <https://aerobasegroup.com/nsn/5305-01-302-9454>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.125 inches

Fastener Length:

0.312 inches

Head Style:

Pan no. 2

Head Diameter:

0.212 inches

Head Height:

Between 0.070 inches and 0.080 inches

Locking Feature:

Pellet threads

First Diameter From Head:

Between 0.075 inches and 0.080 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.187 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Externally Relieved Body Diameter Quantity:

1

Color:

Black fastener

Material:

Steel comp 301 fastener or steel comp 302 fastener or steel comp 302b fastener or steel comp 303 fastener or steel comp 303se fastener or steel comp 304 fastener or steel comp 304l fastener or steel comp 305 fastener or steel comp 308 fastener or steel comp 309 fastener or steel comp 309s fastener or steel comp 310 fastener or steel comp 310s fastener or steel comp 314 fastener or steel comp 316 fastener or steel comp 316l fastener or steel comp 317 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 348 fastener or steel comp 384 fastener or steel comp 385 fastener

Surface Treatment:

Oxide fastener

Surface Treatment Specification:

Mil-c-13924, cl 4 military specification single treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.