## NSN 5305-01-302-9465

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-302-9465 **Thread Direction:** Right-hand Thread Length: Between 8.5 millimeters and 9.5 millimeters Fastener Length: Between 16.7 millimeters and 17.3 millimeters **Head Style:** Flat countersunk **Head Diameter:** Between 9.0 millimeters and 10.0 millimeters **Grip Diameter:** Between 4.978 millimeters and 4.990 millimeters **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 5.0 millimeters **Grip Length:** Between 7.8 millimeters and 8.2 millimeters **Thread Pitch In Millimeters:** 8.0 **External Thread Tolerance Class:** 4h6h **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Surface Finish:** 0.8 micrometers threads Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Mj

,

**Specification Data:** 

80205-na0042 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-302-9465

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0