

View Online at <https://aerobasegroup.com/nsn/5305-01-302-9465>

Thread Direction:

Right-hand

Thread Length:

Between 8.5 millimeters and 9.5 millimeters

Fastener Length:

Between 16.7 millimeters and 17.3 millimeters

Head Style:

Flat countersunk

Head Diameter:

Between 9.0 millimeters and 10.0 millimeters

Grip Diameter:

Between 4.978 millimeters and 4.990 millimeters

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

5.0 millimeters

Grip Length:

Between 7.8 millimeters and 8.2 millimeters

Thread Pitch In Millimeters:

0.8

External Thread Tolerance Class:

4h6h

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Surface Finish:

0.8 micrometers threads

Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Mj

Specification Data:

80205-na0042 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0