NSN 5305-01-302-9466

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-302-9466

Inread Direction:
Right-hand
Thread Length:
Between 7.0 millimeters and 8.0 millimeters
Fastener Length:
Between 9.2 millimeters and 9.8 millimeters
Head Style:
Pan no. 2
Head Diameter:
Between 7.7 millimeters and 8.0 millimeters
Head Height:
Between 2.2 millimeters and 2.4 millimeters
Grip Diameter:
Between 3.978 millimeters and 3.990 millimeters
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
4.0 millimeters
Grip Length:
Between 1.8 millimeters and 2.2 millimeters
Thread Pitch In Millimeters:
0.7
External Thread Tolerance Class:
4h6h
Surface Finish:
0.8 micrometers threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Мј
Specification Data:
80205-na0046 professional/industrial association standard
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5305-01-302-9466

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0