NSN 5305-01-303-5623

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-303-5623 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.590 inches and 1.750 inches **Fastener Length:** Between 1.690 inches and 1.750 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.190 inches Width Between Flats: Between 0.367 inches and 0.375 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Hardness Rating:** 40.0 rockwell c and 50.0 rockwell c **Primary Washer Outside Diameter:** Between 0.494 inches and 0.510 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.023 inches and 0.028 inches Material: Steel **Material Specification:** Sae j489 gr 2 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Thread Series Designator:** Unc **Specification Or Standard:**

A type and 2 grade

NSN 5305-01-303-5623

Assembled Washer Screw - Page 2 of 2



-			
٠.	hΔ	Iŧ.	ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0