NSN 5305-01-303-6730

Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-303-6730



Thread Class: За **Thread Direction:** Right-hand Thread Length: 0.333 inches **Fastener Length:** Between 0.766 inches and 0.811 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.496 inches and 0.510 inches **Head Height:** 0.073 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees **Primary Washer Outside Diameter:** Between 0.278 inches and 0.286 inches **Primary Washer Style:** Flat **Special Features:** Furnished w/one o ring Material: Steel comp 4037 fastener **Material Specification:** Qq-s-624 federal specification single material response fastener **Surface Treatment:** Cadmium fastener **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response fastener **Thread Series Designator:** Unf

NSN 5305-01-303-6730

Assembled Washer Screw - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0