
Assembled Washer Screw - Page 1 of 2





Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.375 inches and 1.500 inches

Fastener Length:

1.500 inches

Head Style:

Hexagon

Head Height:

Between 0.270 inches and 0.295 inches

Width Between Flats:

Between 0.551 inches and 0.562 inches

Washer Quantity:

1

Internal Drive Style:

Slot

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

16

Hardness Rating:

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.670 inches and 0.694 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.032 inches and 0.040 inches

Material:

Steel primary washer

Material Specification:

Sae j429 gr 2 assn standard single material response fastener

Surface Treatment:

Cadmium fastener or zinc fastener

Surface Treatment Specification:

Ams 2400 assn standard 1st treatment response fastener or ams 2402 assn standard 2nd treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

NSN 5305-01-303-8726

Assembled Washer Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0