Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-303-8731



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.337 inches and 0.387 inches Fastener Length: Between 0.472 inches and 0.502 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.190 inches Grip Length: Between 0.115 inches and 0.135 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life:

N/a

## Unit Of Measure:

## NSN 5305-01-303-8731

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

