NSN 5305-01-303-9653

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-303-9653

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.381 inches and 0.431 inches
Fastener Length:
Between 0.579 inches and 0.609 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.376 inches and 0.385 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.178 inches and 0.198 inches
Features Provided:
Cetyl alcohol lubricant
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Stainless steel
Surface Treatment:
Aluminum and chromate
Surface Treatment Specification:
Mil-c-83488 type 2 cl 3 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
No

NSN 5305-01-303-9653

Close Tolerance Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-c-83488 spec.